

Motorcycle Batteries

*Scroll down for EB PP/Dry Series, LT ABS/Wet Series, EB PP/Wet Series, High Performance Flooded and Conventional Flooded

LT PP/Dry Series

Dry Charged AGM VRLA Maintenance Free type--PP case

General Features

1. High Capacity ,Long life.
2. Sealing structure of PP materials.
3. High CCA and good starting performance.
4. Good charging acceptance and vibration resistant performance.
5. Application of AGM technology.
6. Application of COS and TTP.
7. Advanced sulfate-resistant technology.
8. Advanced calcium lead alloy technology, maintenance-free design.
9. Dependable design of leakage resistant and valve regulated sealing.
10. Dry charged design, long storage time and can be used at any time you want.
11. full ranges models, good appearance and high standard design.


Typical Applications

1. ATV.
2. Jet ski.
3. Motorcycle.
4. Snowmobile.
5. Lawn & Garden.

Specifications

Model	Voltage (V)	Capacity C10 AH	CCA @°F (-18°C)	Battery Size						Terminal	Weight (without acid)		Electrolyte		Total weight	Charging current
				mm (±2mm)			inch (±1/16in)				Kg	Lbs	Volume liters	Weight Kg		
				A	L	W	H	L	W						H	
6LT4-BS	6	4	N/A	70	70	95	2 3/4	2 3/4	3 3/4	/	0.67	1.5	0.1	0.18	0.84	0.4
LT2.5L-BS	12	2.5	25	80	70	105	3 1/8	2 3/4	4 1/8	/	0.92	2	0.2	0.23	1.15	0.3
LT2.5L-BS-1 (J)	12	2.5	20	80	70	105	3 1/8	2 3/4	4 1/8	/	0.8	1.8	0.2	0.24	1.04	0.3
LT3L-BS	12	3	35	98	56	110	3 7/8	2 3/16	4 5/16	B	0.99	2.2	0.2	0.25	1.24	0.3
LTR4A-BS	12	2.3	45	113	48	85	4 7/16	1 7/8	3 3/8	I	0.82	1.8	0.1	0.17	0.99	0.2
LT4B-BS	12	2.3	40	113	38	85	4 7/16	1 1/2	3 3/8	J	0.79	1.7	0.1	0.14	0.93	0.2
LTX4L-BS	12	3	50	113	70	85	4 7/16	2 3/4	3 3/8	A	1.21	2.7	0.2	0.25	1.45	0.3
LT4AL-BS	12	4	60	120	70	92	4 3/4	2 3/4	3 5/8	A	1.3	2.9	0.2	0.32	1.62	0.4
LTX5L-BS	12	4	70	113	70	105	4 4/8	2 3/4	4 1/8	A	1.47	3.2	0.2	0.32	1.79	0.4
LT5AL-BS	12	5	70	120	60	130	4 6/8	2 1/4	5 1/8	B	1.48	3.3	0.3	0.38	1.86	0.5
LTX7A-BS	12	6	90	150	87	93	5 7/8	3 2/4	3 5/8	A	2	4.4	0.4	0.48	2.48	0.6

LTX7L-BS	12	6	85	113	70	130	⁴ / _{7/16}	2 3/4	5 1/8	A	1.97	4.3	0.3	0.42	2.39	0.6
LT7D-BS	12	7	85	146	60	130	5 6/8	2 1/4	5 1/8	B	1.86	4.1	0.4	0.48	2.34	0.7
LT7DL-BS	12	7	85	146	60	130	5 6/8	2 3/8	5 1/8	B	1.86	4.1	0.4	0.48	2.34	0.7
LTX9-BS	12	8	120	150	87	105	5 7/8	3 7/16	4 1/8	A	2.45	5.4	0.4	0.58	3.03	0.8
LT9A-BS	12	9	120	135	75	139	5 3/8	² / _{15/16}	5 1/2	B	2.46	5.4	0.5	0.66	3.11	0.9
LTX10L-BS	12	10	160	135	90	145	⁵ / _{5/16}	3 9/16	⁵ / _{11/16}	A	2.84	6.3	0.7	0.93	3.77	1
LTX12-BS	12	10	180	150	87	130	5 7/8	3 7/16	5 1/8	A	3.05	6.7	0.6	0.8	3.85	1
LTX12L-BS	12	10	180	150	87	130	5 7/8	3 7/16	5 1/8	A	3.05	6.7	0.6	0.8	3.85	1
LTX14-BS	12	12	200	150	87	145	5 7/8	3 7/16	⁵ / _{11/16}	A	3.5	7.7	0.7	0.91	4.41	1.2
LTX14L-BS	12	12	200	150	87	145	5 7/8	3 7/16	⁵ / _{11/16}	A	3.5	7.7	0.7	0.91	4.41	1.2
LTX14AH-BS	12	12	210	135	90	164	⁵ / _{5/16}	3 9/16	6 7/16	A	3.71	8.2	0.7	0.91	4.62	1.2
LTX14AHL-BS	12	12	210	135	90	164	⁵ / _{5/16}	3 9/16	6 7/16	A	3.74	8.2	0.7	0.91	4.65	1.2
LTX15-BS	12	13	230	175	87	130	6 7/8	3 7/16	5 1/8	A	3.7	8.1	0.7	0.98	4.68	1.3



Model	Voltage (V)	Capacity C10 AH	CCA		Battery Size						Terminal	Weight (without acid)		Electrolyte		Total weight Kg	Charging current A
			@°F (-18°C)		mm (±2mm)			inch (±1/16in)				Kg	Lbs	liters	Kg		
			A	L	W	H	L	W	H								
LTX16-BS	12	14	230	150	87	161	5 7/8	3 7/16	⁶ / _{5/16}	A	4.05	8.9	0.8	1.03	5.08	1.4	
LTX16L-BS	12	14	230	150	87	161	5 7/8	3 7/16	⁶ / _{5/16}	A	4.06	9	0.8	1.03	5.1	1.4	
LTX16-BS-1	12	14	230	150	87	161	5 7/8	3 7/16	⁶ / _{5/16}	E	4.01	8.8	0.8	1.03	5.05	1.4	
LT16CL-BS	12	19	260	175	100	175	6 7/8	³ / _{15/16}	6 7/8	A	5.22	11.5	1	1.34	6.55	1.9	
LTX18-BS	12	18	250	205	87	162	⁸ / _{1/16}	3 7/16	6 3/8	A	5.08	11.2	1.1	1.51	6.59	1.8	
LTX18L-BS	12	18	250	205	87	162	⁸ / _{1/16}	3 7/16	6 3/8	A	5.08	11.2	1.1	1.51	6.59	1.8	
LTX20-BS	12	18	270	175	87	155	6 7/8	3 7/16	6 1/8	A	4.73	10.4	0.9	1.19	5.92	1.8	
LTX20L-BS	12	18	270	175	87	155	6 7/8	3 7/16	6 1/8	A	4.75	10.5	0.9	1.19	5.94	1.8	
LTX20CH-BS	12	18	270	150	87	161	5 7/8	3 7/16	⁶ / _{5/16}	A	4.51	9.9	0.8	1.11	5.63	1.8	

LTX20H-BS	12	18	310	175	87	155	6 7/8	3 7/16	6 1/8	A	4.87	10.7	0.9	1.26	6.12	1.8
LTX20HL-BS	12	18	310	175	87	155	6 7/8	3 7/16	6 1/8	A	4.89	10.8	0.9	1.26	6.14	1.8
LTX20HL-BS-PW	12	18	310	175	87	175	6 7/8	3 7/16	6 7/8	A	4.96	10.9	0.9	1.26	6.21	1.8
LTX24H-BS	12	21	350	205	87	162	8 1/16	3 7/16	6 3/8	A	5.77	12.7	1.1	1.43	7.2	2.1
LTX24HL-BS	12	21	350	205	87	162	8 1/16	3 7/16	6 3/8	A	5.77	12.7	1.1	1.43	7.2	2.1

EB PP/Dry Series

Dry Charged AGM VRLA Maintenance Free type -- PP case, Battery terminal setting into battery cover.

General Features

1. Injection molding structure of battery terminal and battery cover.
2. Sealing structure of PP materials.
3. High capacity ,Long life.
4. High CCA and good starting performance.
5. Good charging acceptance and vibration resistant performance.
6. Application of AGM technology.
7. Application of COS and TTP.
8. Advanced sulfate-resistant technology.
9. Advanced calcium lead alloy technology, maintenance-free design.
10. Dependable design of leakage resistant and valve regulated sealing.
11. Dry charged design, long storage time and can be used at any time you want.
12. full ranges models, good appearance and high standard design.

Typical Applications

1. ATV.
2. Jet ski.
3. Motorcycle.
4. Snowmobile.
5. Lawn & Garden.

Specifications

Model	Voltage	Capacity C10	CCA	Dimension						Terminal	Weight(without acid)		Electrolyte		Total weight	Charging current
	v		@°F	mm(±2mm)			inch(±1/16in)				Kg	Lbs	Voltage	Weight		
		(-18°C)	A	L	W	H	L	W	H	liters			Kg	Kg	A	
	Ah															
EBX4L-BS	12	3	50	113	70	85	4 7/16	2 3/4	3 1/2	A	1.23	2.7	0.2	0.25	1.48	0.3
EBX5L-BS	12	4	70	113	70	105	4 7/16	2 3/4	4	A	1.48	3.3	0.2	0.32	1.8	0.4
EBZ5L-BS	12	3.5	65	113	70	85	4 7/16	2 3/4	3 1/2	A	1.23	2.7	0.2	0.25	1.48	0.4

EBZ6L-BS	12	5	90	113	70	105	$\frac{4}{7/16}$	2 3/4	4 1/8	A	1.73	3.8	0	0	1.73	0.5
EBX7L-BS	12	6	85	113	70	130	$\frac{4}{7/16}$	2 3/4	5	A	1.96	4.3	0.3	0.45	2.4	0.6
EBX7A-BS	12	6	90	150	87	93	5 7/8	3 7/16	$\frac{3}{11/16}$	A	1.99	4.4	0.4	0.48	2.48	0.6
EB7B-BS	12	6.5	85	150	66	93	5 7/8	2 5/8	$\frac{3}{11/16}$	A	2	4.4	0.3	0.45	2.44	0.7
EBZ7L-BS	12	6	130	113	70	105	$\frac{4}{7/16}$	2 3/4	4 1/8	A	1.87	4.1	0.3	0.4	2.27	0.6
EBX9-BS	12	8	120	150	87	105	5 7/8	3 1/2	4 1/8	A	2.49	5.5	0.4	0.58	3.07	0.8
EB9A-BS	12	9	120	135	75	139	$\frac{5}{5/16}$	$\frac{2}{15/16}$	5 1/2	A	2.49	5.5	0.5	0.65	3.14	0.9
EB9B-BS	12	8	115	150	70	105	5 7/8	2 3/4	4 1/8	A	2.38	5.2	0.4	0.56	2.93	0.8
EBX10L-BS	12	10	160	135	90	145	$\frac{5}{5/16}$	3 9/16	$\frac{5}{11/16}$	A	2.91	6.4	0.7	0.92	3.83	1
EBZ10-BS	12	8.6	190	150	88	93	5 7/8	3 7/16	$\frac{3}{11/16}$	A	2.85	6.3	0.4	0.58	3.43	0.9
EBZ12-BS	12	11	210	150	88	110	5 7/8	3 7/16	4 5/16	A	3.37	7.4	0.5	0.66	4.03	1.1
EBZ14-BS	12	11.2	230	150	88	110	5 7/8	3 7/16	4 5/16	A	3.37	7.4	0.5	0.66	4.03	1.1
EBX12L-BS	12	10	180	150	87	130	5 7/8	3 7/16	5 1/8	A	3.14	6.9	0.6	0.8	3.93	1
EBX12-BS	12	10	180	150	87	130	5 7/8	3 7/16	5 1/8	A	3.14	6.9	0.6	0.8	3.93	1
EB12A-BS	12	10	175	150	88	105	5 7/8	3 7/16	4 1/8	A	2.7	6	0.5	0.68	3.38	1
EB12B-BS	12	10	175	150	70	130	5 7/8	2 3/4	5 1/8	A	3.09	6.8	0.6	0.8	3.89	1
EBX14L-BS	12	12	200	150	87	145	5 7/8	3 7/16	$\frac{5}{11/16}$	A	3.57	7.9	0.7	0.91	4.47	1.2
EBX14-BS	12	12	200	150	87	145	5 7/8	3 7/16	$\frac{5}{11/16}$	A	3.57	7.9	0.7	0.91	4.47	1.2
EB14B-BS	12	12	210	150	70	145	5 7/8	2 3/4	$\frac{5}{11/16}$	A	3.5	7.7	0.7	0.87	4.38	1.2
EBX14AHL-BS	12	12	210	135	90	164	$\frac{5}{5/16}$	3 9/16	6 7/16	A	4.03	8.9	0.6	0.86	4.88	1.2
EBX14AH-BS	12	12	210	135	90	164	$\frac{5}{5/16}$	3 9/16	6 7/16	A	4.03	8.9	0.6	0.86	4.88	1.2
EBX15L-BS	12	13	230	175	87	130	6 7/8	3 7/16	5 2/16	A	3.74	8.2	0.7	0.99	4.73	1.3

Model	Voltage V	Capacity C10 Ah	CCA		Dimension						Terminal	Weight(without acid)		Electrolyte		Total weight Kg	Charging current A
			@°F	@°C	mm(±2mm)			inch(±1/16in)				Kg	Lbs	Voltage liters	Weight Kg		
			(-18°C)	A	L	W	H	L	W	H							
EBX15-BS	12	13	230	175	87	130	6 7/8	$\frac{3}{7/16}$	$\frac{5}{2/16}$	A	3.74	8.2	0.7	0.99	4.73	1.3	
EBX16L-BS	12	14	230	150	87	161	5 7/8	$\frac{3}{7/16}$	$\frac{6}{5/16}$	A	4.1	9	0.8	1.03	5.14	1.4	
EBX16-BS	12	14	230	150	87	161	5 7/8	$\frac{3}{7/16}$	$\frac{6}{5/16}$	A	4.1	9	0.8	1.03	5.14	1.4	

EBX16-BS-1	12	14	230	150	87	161	5 7/8	3 7/16	6 5/16	E	4.1	9	0.8	1.03	5.13	1.4
EB16BL-BS	12	19	260	175	100	155	6 7/8	3 15/16	6 2/16	A	5.22	11.5	1	1.34	6.55	1.9
EB16B-BS	12	19	260	175	100	155	6 7/8	3 15/16	6 2/16	A	5.22	11.5	1	1.34	6.55	1.9
EBX18L-BS	12	18	250	205	87	162	8 1/16	3 7/16	6 3/8	A	5.13	11.3	1.1	1.48	6.61	1.8
EBX18-BS	12	18	250	205	87	162	8 1/16	3 7/16	6 3/8	A	5.13	11.3	1.1	1.48	6.61	1.8
EBX20L-BS	12	18	270	175	87	155	6 7/8	3 7/16	6 2/16	A	4.98	11	0.9	1.26	6.23	1.8
EBX20-BS	12	18	270	175	87	155	6 7/8	3 7/16	6 2/16	A	4.98	11	0.9	1.26	6.23	1.8
EBX20HL-BS	12	18	310	175	87	155	6 7/8	3 7/16	6 2/16	A	4.98	11	0.9	1.26	6.23	1.8
EBX20H-BS	12	18	310	175	87	155	6 7/8	3 7/16	6 2/16	A	4.98	11	0.9	1.26	6.23	1.8
EBX20CH-BS	12	18	270	150	87	161	5 7/8	3 7/16	6 5/16	A	4.59	10.1	0.8	1.11	5.7	1.8
EBX20PL-BS	12	18	275	182	77	168	7 1/8	3 1/16	6 1/2	G	4.71	10.4	0.9	1.13	5.84	1.8
EBX24HL-BS	12	21	350	205	87	162	8 1/16	3 7/16	6 3/8	A	5.82	12.8	1.1	1.43	7.25	2.1
EBX24H-BS	12	21	350	205	87	162	8 1/16	3 7/16	6 3/8	A	5.82	12.8	1.1	1.43	7.25	2.1
EBX30L-BS	12	30	385	166	126	173	6 1/2	4 15/16	6 3/4	A	8.04	17.7	1.4	1.86	9.9	3
EBX30-BS	12	30	385	166	126	173	6 1/2	4 15/16	6 3/4	A	8.04	17.7	1.4	1.86	9.9	3

LT ABS/Wet Series

Wet charged AGM VRLA Maintenance Free type--ABS case

General Features

1. ABS material plastic sealing construction.
2. Fully charged in factory with acid.
3. High Capacity, Long life.
4. High CCA and good starting performance.
5. Good charging acceptance and vibration resistant performance.
6. Low self-discharge.
7. Application of AGM technology, no flow electrolyte.
8. Application of COS and TTP.
9. Advanced sulfate-resistant technology.
10. Advanced calcium lead alloy technology, maintenance-free design.
11. Reliable seal and valve regulated design.
12. Full ranges models, good appearance and high standard design.

Typical Applications

1. ATV
2. Jet ski
3. Motorcycle
4. Snowmobile
5. Lawn & Garden

Specifications

Models	Voltage V	Capacity C10 Ah	CCA @°F (-18°C) A	Dimension						Terminal	Weight(with acid)		Charging current A
				mm(±2mm)			inch(±1/16in)				Kg	Lbs	
				L	W	H	L	W	H				
6LT4-2	6	4	N/A	70	70	95	2 3/4	2 3/4	3 3/4	/	0.86	1.9	0.4
LT2.5-3	12	2.5	25	80	70	105	3 1/8	2 3/4	4 1/8	/	1.17	2.6	0.3
LT2.5-3-1(J)	12	2.5	20	80	70	105	3 1/8	2 3/4	4 1/8	/	1.06	2.3	0.3
LT3-3	12	3	35	98	56	110	3 7/8	2 3/16	4 5/16	B	1.3	2.9	0.3
LTR4A-5	12	2.3	45	113	48	85	4 7/16	1 7/8	3 3/8	I	0.96	2.1	0.2
LT4B-5	12	2.3	40	113	38	85	4 7/16	1 1/2	3 3/8	J	0.93	2	0.2
LT4-3	12	3	50	113	70	85	4 7/16	2 3/4	3 1/2	A	1.47	3.2	0.3
LT4A-3	12	4	60	120	70	92	4 3/4	2 3/4	3 5/8	A	1.62	3.6	0.4
LT5-3	12	4	70	113	70	105	4 7/16	2 3/4	4 1/8	A	1.8	4	0.4
LT5A-3-1	12	5	70	119	59	130	4.75	2 3/8	5 1/8	B	1.85	4.1	0.5
LT6.5-3	12	6.5	85	139	66	102	5 1/2	2 5/8	4	B	2.32	5.1	0.7
LT7-3	12	6	85	113	70	130	4 7/16	2 3/4	5 1/8	A	2.41	5.3	0.6
LT7A-4	12	6	90	150	87	93	5 7/8	3 7/16	3 11/16	A	2.49	5.5	0.6
LT7B-4	12	6.5	85	150	65	93	5 7/8	2 9/16	3 11/16	A	2.33	5.1	0.7
LT7D-3	12	7	85	146	60	130	5 1/2	2.375	5 1/8	B	2.35	5.2	0.7
LT7D-4	12	7	85	146	60	130	5 3/4	2.375	5 1/8	B	2.35	5.2	0.7
LT7E-4	12	7	90	136	75	122	5 3/8	3	4 3/4	B	2.95	6.5	0.7
LTZ7-3	12	6	130	113	70	105	4 7/16	2 3/4	4 1/8	A	2.02	4.4	0.6
LT9-4	12	8	120	150	87	105	5 7/8	3 7/16	4 1/8	A	3.08	6.8	0.8
LT9A-4	12	9	120	135	75	139	5 5/16	2 15/16	5 1/2	B	3.03	6.7	0.9
LT9B-4	12	8	115	150	68	105	5 7/8	2 11/16	4 1/8	A	2.77	6.1	0.8
LT10-3	12	10	160	135	90	145	5 5/16	3 9/16	5 11/16	A	3.83	8.4	1
LTZ10-4	12	8.6	190	150	87	93	5 7/8	3 7/16	3 11/16	A	2.9	6.4	0.9
LT12A-4	12	10	175	150	87	105	5 7/8	3 7/16	4 1/8	A	3.38	7.4	1
LT12B-4	12	10	175	150	69	130	5 7/8	2 11/16	5 1/8	A	3.59	7.9	1
LT12-3	12	10	180	150	87	130	5 7/8	3 7/16	5 1/8	A	3.92	8.6	1
LT12-4	12	10	180	150	87	130	5 7/8	3 7/16	5 1/8	A	3.92	8.6	1

Models	Voltage V	Capacity		Dimension						Terminal	Weight(with acid)		Charging current
		C10	CCA	mm(±2mm)			inch(±1/16in)				Kg	Lbs	
			@°F (-18°C)	Ah	A	L	W	H	L				W
LTZ12-4	12	11	210	150	87	110	5 7/8	3 7/16	4 5/16	A	3.39	7.5	1.1
LT14-3	12	12	200	150	87	145	5 7/8	3 7/16	5 11/16	A	4.49	9.9	1.2
LT14-4	12	12	200	150	87	145	5 7/8	3 7/16	5 11/16	A	4.48	9.9	1.2
LT14A-4	12	12	210	135	90	167	5 5/16	3 9/16	6 9/16	A	4.73	10.4	1.2
LT14A-3	12	12	210	135	90	167	5 5/16	3 9/16	6 9/16	A	4.73	10.4	1.2
LT14B-4	12	12	210	150	69	145	5 7/8	2 11/16	5 11/16	A	4.15	9.1	1.2
LTZ14-4	12	11.2	230	150	87	110	5 7/8	3 7/16	4 5/16	A	3.59	7.9	1.1
LT15-3	12	13	230	175	87	130	6 7/8	3 7/16	5 1/8	A	4.71	10.4	1.3
LT15-4	12	13	230	175	87	130	6 7/8	3 7/16	5 1/8	A	4.69	10.3	1.3
LT16-3	12	14	230	150	87	161	5 7/8	3 7/16	6 5/16	A	5.19	11.4	1.4
LT16-4	12	14	230	150	87	161	5 7/8	3 7/16	6 5/16	A	5.18	11.4	1.4
LT16A-4	12	14	230	150	87	161	5 7/8	3 7/16	6 5/16	E	5.14	11.3	1.4
LT16C-3	12	19	260	175	100	175	6 7/8	3 15/16	6 7/8	A	6.66	14.7	1.9
LT18-3	12	18	250	205	87	162	8 1/16	3 7/16	6 3/8	A	6.64	14.6	1.8
LT18-4	12	18	250	205	87	162	8 1/16	3 7/16	6 3/8	A	6.64	14.6	1.8
LT20-3	12	18	270	175	87	155	6 7/8	3 7/16	6 1/8	A	5.98	13.2	1.8
LT20-4	12	18	270	175	87	155	6 7/8	3 7/16	6 1/8	A	5.96	13.1	1.8
LT20H-3	12	18	310	175	87	155	6 7/8	3 7/16	6 1/8	A	6.19	13.6	1.8
LT20H-4	12	18	310	175	87	155	6 7/8	3 7/16	6 1/8	A	6.17	13.6	1.8
LT20CH-4	12	18	270	150	87	161	5 7/8	3 7/16	6 5/16	A	5.71	12.6	1.8
LT24-3	12	21	350	205	87	162	8 1/16	3 7/16	6 3/8	A	7.31	16.1	2.1
LT24-4	12	21	350	205	87	162	8 1/16	3 7/16	6 3/8	A	7.3	16.1	2.1
LT24-3-1	12	21	350	205	87	162	8 1/16	3 7/16	6 3/8	C	7.3	16.1	2.1
LT30-3	12	30	385	165	125	175	6 1/2	4 15/16	6 7/8	A	10	22	3
LT30-4	12	30	385	165	125	175	6 1/2	4 15/16	6 7/8	A	10	22	3

EB PP/Wet Series

Wet Charged AGM VRLA Maintenance Free type --PP case,Battery terminal setting into battery cover.

General Features

1. Injection molding structure of battery terminal and battery cover.
2. Sealing structure of PP materials.
3. High capacity ,Long life.
4. High CCA and good starting performance.
5. Good charging acceptance and vibration resistant performance.
6. Application of AGM technology.
7. Application of COS and TTP.
8. Advanced sulfate-resistant technology.
9. Advanced calcium lead alloy technology, maintenance-free design.
10. Dependable design of leakage resistant and valve regulated sealing.

11. Dry charged design, long storage time and can be used at any time you want.
12. full ranges models, good appearance and high standard design.

Typical Applications

1. ATV.
2. Jet ski.
3. Motorcycle.
4. Snowmobile.
5. Lawn & Garden.

Specifications

Models	Voltage V	Capacity C10 Ah	CCA	Dimension						Terminal	Weight(with acid)		Charging current A
			@°F (-18°C)	mm(±2mm)			inch(±1/16in)				Kg	Lbs	
			A	L	W	H	L	W	H				
EB4-3	12	3	50	113	70	85	4 7/16	2 3/4	3 1/2	A	1.47	3.2	0.3
EB5-3	12	4	70	113	70	105	4 7/16	2 3/4	4	A	1.78	3.9	0.4
EBZ5-3	12	3.5	65	113	70	85	4 7/16	2 3/4	3 1/2	A	1.47	3.2	0.4
EBZ6-3	12	5	90	113	70	105	4 7/16	2 3/4	4 1/8	A	2.02	4.4	0.5
EB7-3	12	6	85	113	70	130	4 7/16	2 3/4	5	A	2.41	5.3	0.6
EB7A-4	12	6	90	150	87	93	5 7/8	3 7/16	3 11/16	A	2.48	5.5	0.6
EB7B-4	12	6.5	85	150	66	93	5 7/8	2 5/8	3 11/16	A	2.46	5.4	0.7
EBZ7-3	12	6	130	113	70	105	4 7/16	2 3/4	4 1/8	A	2.27	5	0.6
EB9-4	12	8	120	150	87	105	5 7/8	3 1/2	4 1/8	A	3.06	6.7	0.8
EB9A-4	12	9	120	135	75	139	5 5/16	2 15/16	5 1/2	A	3.16	7	0.9
EB9B-4	12	8	115	150	70	105	5 7/8	2 3/4	4 1/8	A	2.95	6.5	0.8
EB10-3	12	10	160	135	90	145	5 5/16	3 9/16	5 11/16	A	3.83	8.4	1
EBZ10-4	12	8.6	190	150	88	93	5 7/8	3 7/16	3 11/16	A	3.45	7.6	0.9
EB12-3	12	10	180	150	87	130	5 7/8	3 7/16	5 1/8	A	3.95	8.7	1
EB12-4	12	10	180	150	87	130	5 7/8	3 7/16	5 1/8	A	3.95	8.7	1
EB12A-4	12	10	175	150	88	105	5 7/8	3 7/16	4 1/8	A	3.37	7.5	1
EB12B-4	12	10	175	150	70	130	5 7/8	2 3/4	5 1/8	A	3.71	8.6	1
EBZ12-4	12	12	210	150	88	110	5 7/8	3 7/16	4 5/16	A	4.05	9	1.2
EBZ12A-4	12	11	210	150	88	110	5 7/8	3 7/16	4 5/16	A	4.06	8.9	1.1
JB14-4	12	14	200	150	87	145	5 7/8	3 7/16	5 11/16	/	4.8	10.6	1.2
EB14A-3	12	12	210	135	90	164	5 5/16	3 9/16	6 7/16	A	4.87	10.7	1.2
EB14A-4	12	12	210	135	90	164	5 5/16	3 9/16	6 7/16	A	4.87	10.7	1.2
EB14B-4	12	12	210	150	70	145	5 7/8	2 3/4	5 11/16	A	4.39	9.7	1.2
EB14C-3	12	12	200	150	87	145	5 7/8	3 7/16	5 11/16	A	4.47	9.9	1.2
EB14C-4	12	12	200	150	87	145	5 7/8	3 7/16	5 11/16	A	4.47	9.9	1.2

Models	Voltage V	Capacity C10 Ah	CCA	Dimension						Terminal	Weight(with acid)		Charging current A
			@°F (- 18°C) A	mm(±2mm)			inch(±1/16in)				Kg	Lbs	
			L	W	H	L	W	H					
EBZ14A-4	12	11.2	230	150	88	110	5 7/8	3 7/16	4 5/16	A	4.07	9	1.1
EB15-3	12	13	230	175	87	130	6 7/8	3 7/16	5 2/16	A	4.7	10.3	1.3
EB15-4	12	13	230	175	87	130	6 7/8	3 7/16	5 2/16	A	4.7	10.3	1.3
EB16-3	12	14	230	150	87	161	5 7/8	3 7/16	6 5/16	A	5.15	11.3	1.4
EB16-4	12	14	230	150	87	161	5 7/8	3 7/16	6 5/16	A	5.15	11.3	1.4
EB16A-4	12	14	230	150	87	161	5 7/8	3 7/16	6 5/16	E	5.13	11.3	1.4
EB16B-3	12	19	260	175	100	155	6 7/8	3 15/16	6 2/16	A	6.56	14.4	1.9
EB16B-4	12	19	260	175	100	155	6 7/8	3 15/16	6 2/16	A	6.56	14.4	1.9
EB18-3	12	18	250	205	87	162	8 1/16	3 7/16	6 3/8	A	6.59	14.5	1.8
EB18-4	12	18	250	205	87	162	8 1/16	3 7/16	6 3/8	A	6.59	14.5	1.8
EB20-3	12	18	270	175	87	155	6 7/8	3 7/16	6 2/16	A	6.25	13.8	1.8
EB20-4	12	18	270	175	87	155	6 7/8	3 7/16	6 2/16	A	6.25	13.8	1.8
EB20H-3	12	18	310	175	87	155	6 7/8	3 7/16	6 2/16	A	6.25	13.8	1.8
EB20H-4	12	18	310	175	87	155	6 7/8	3 7/16	6 2/16	A	6.25	13.8	1.8
EB20CH-4	12	18	270	150	87	161	5 7/8	3 7/16	6 5/16	A	5.73	12.6	1.8
EB20P-3	12	18	275	182	77	168	7 1/8	3 1/16	6 10/16	G	5.79	12.8	1.8
EB24-3	12	21	350	205	87	162	8 1/8	3 7/16	6 6/16	A	7.26	16	2.1
EB24-4	12	21	350	205	87	162	8 1/16	3 7/16	6 3/8	A	7.27	16	2.1
EB30-3	12	30	385	165	125	173	6 1/2	4 15/16	6 3/4	A	9.91	21.8	3
EB30-4	12	30	385	165	125	173	6 1/2	4 15/16	6 3/4	A	9.91	21.8	3

High Performance Flooded

General Features

1. Super higher CCA, Super starting performance.
2. High-quality composite of Fiber Glass and PE separators Application.
3. Reliable Design of Liquid-hole plug seal.
4. Adopt advanced low antimony alloy and low maintenance design.
5. High Capacity, Long life.
6. Good charging acceptance and vibration resistant performance.
7. Application of TTP technology.
8. Advanced sulfate-resistant technology.
9. Seal design with reliable plugs.
10. Dry charged design, long storage time, can be used at any time you want.
11. full ranges models, good appearance and high standard design.

Typical Applications

1. ATV.
2. Jet ski.
3. Motorcycle.
4. Snowmobile.
5. Lawn & Garden.

Specifications

Model	Voltage V	Capacity C10 Ah	CCA @°F (- 18°C) A	Dimension						Terminal	Weight(without acid)		Electrolyte		Total weight Kg	Charging current A
				mm(±2mm)			inch(±1/16in)				Kg	Lbs	Volume liters	Weight Kg		
				L	W	H	L	W	H							
LB2.5L-C	12	2.5	19	80	70	105	3 1/8	2 3/4	4 1/8	/	0.77	1.7	0.24	0.3	1.07	0.3
LB2.5L-A	12	2.5	19	80	70	105	3 1/8	2 3/4	4 1/8	/	0.77	1.7	0.24	0.3	1.07	0.3
LB2.5L-C-1	12	2.5	19	80	70	105	3 1/8	2 3/4	4 1/8	/	0.77	1.7	0.24	0.3	1.07	0.3
LB2.5L-C-2	12	2.5	19	80	70	105	3 1/8	2 3/4	4 1/8	/	0.84	1.85	0.23	0.29	1.13	0.3
LB3L-A	12	3	32	98	56	110	3 7/8	2 1/4	4 3/8	B	0.95	2.09	0.23	0.29	1.24	0.3
LB3L-B	12	3	32	98	56	110	3 7/8	2 1/4	4 3/8	B	0.95	2.09	0.23	0.29	1.24	0.3
LB4L-B	12	4	56	120	70	92	4 6/8	2 3/4	3 5/8	A	1.23	2.71	0.3	0.38	1.61	0.4
LB4L-A	12	4	56	120	70	92	4 6/8	2 3/4	3 5/8	A	1.23	2.71	0.3	0.38	1.61	0.4
LB5L-B	12	5	65	120	60	130	4 6/8	2 1/4	5 1/8	B	1.53	3.37	0.36	0.46	1.99	0.5
LB5L-B2	12	5	65	120	60	130	4 6/8	2 1/4	5 1/8	A	1.55	3.42	0.36	0.46	2.01	0.5
LB6.5L-B	12	6.5	55	137	66	100	5 3/8	2 2/4	3 7/8	B	1.8	3.97	0.5	0.64	2.44	0.7
LB7-A	12	8	124	135	75	133	5 3/8	3	5 2/8	B	2.16	4.76	0.57	0.73	2.89	0.8
LB7L-A	12	8	124	135	75	133	5 3/8	3	5 2/8	B	2.16	4.76	0.57	0.73	2.89	0.8
LB7L-B	12	8	124	135	75	133	5 3/8	3	5 2/8	B	2.16	4.76	0.57	0.73	2.89	0.8
LB7L-A2	12	8	124	135	75	133	5 3/8	3	5 2/8	A	2.2	4.85	0.57	0.73	2.93	0.8
LB7L-B2	12	8	124	135	75	133	5 3/8	3	5 2/8	A	2.2	4.85	0.57	0.73	2.93	0.8
LB7-A2	12	8	124	135	75	133	5 3/8	3	5 2/8	A	2.2	4.85	0.57	0.73	2.93	0.8
LB7B-B	12	7	124	150	60	130	5 7/8	2 1/4	5 1/8	B	1.9	4.19	0.51	0.65	2.55	0.7
LB7C-A	12	8	124	130	90	114	5 1/8	3 2/4	4 4/8	E	2.15	4.74	0.58	0.74	2.89	0.8
LB9-B	12	9	130	135	75	139	5 3/8	3	5 4/8	B	2.4	5.29	0.56	0.72	3.12	0.9
LB9L-B	12	9	130	135	75	139	5 3/8	3	5 4/8	B	2.4	5.29	0.56	0.72	3.12	0.9
LB9L-A1	12	9	124	135	75	139	5 3/8	3	5 4/8	F	2.43	5.36	0.6	0.77	3.2	0.9
LB9L-A2	12	9	124	135	75	139	5 3/8	3	5 4/8	A	2.43	5.36	0.6	0.77	3.2	0.9
LB9L-B2	12	9	124	135	75	139	5 3/8	3	5 4/8	A	2.43	5.36	0.6	0.77	3.2	0.9
LB9A-A	12	9	124	135	75	155	5 3/8	3	6 1/8	B	2.43	5.36	0.6	0.77	3.2	0.9

Model	Voltage V	Capacity C10 Ah	CCA	Dimension						Terminal	Weight(without acid)		Electrolyte		Total weight Kg	Charging current A
			@°F (- 18°C)	mm(±2mm)			inch(±1/16in)				Kg	Lbs	Volume liters	Weight Kg		
			A	L	W	H	L	W	H							
LB10L-A2	12	11	160	135	90	145	5 3/8	3 1/2	5 3/4	D	3.2	7.05	0.72	0.92	4.12	1.1
LB10L-B	12	11	160	135	90	145	5 3/8	3 1/2	5 3/4	B	3.2	7.05	0.72	0.92	4.12	1.1
LB10L-B2	12	11	160	135	90	145	5 3/8	3 1/2	5 3/4	D	3.2	7.05	0.72	0.92	4.12	1.1
LB10A-A2	12	11	160	135	90	155	5 3/8	3 1/2	6 1/8	D	3.2	7.05	0.72	0.92	4.12	1.1
LB12A-A	12	12	165	134	80	160	5 2/8	3 1/4	6 2/8	B	3.25	7.16	0.72	0.92	4.17	1.2
LB12A-B	12	12	165	134	80	160	5 2/8	3 1/4	6 2/8	B	3.25	7.16	0.72	0.92	4.17	1.2
LB12AL-A	12	12	165	134	80	160	5 2/8	3 1/4	6 2/8	B	3.25	7.16	0.7	0.9	4.15	1.2
LB12AL-A1	12	12	165	134	80	160	5 2/8	3 1/4	6 2/8	A	3.25	7.16	0.7	0.9	4.15	1.2
LB12AL-A2	12	12	165	134	80	160	5 2/8	3 1/4	6 2/8	B	3.25	7.16	0.72	0.92	4.17	1.2
LB12B-B2	12	12	165	160	90	130	6 2/8	3 2/4	5 1/8	D	3.2	7.05	0.77	0.99	4.19	1.2
LB12C-A	12	12	165	134	80	175	5 2/8	3 1/4	6 7/8	A	3.25	7.16	0.72	0.92	4.17	1.2
LB14-A2	12	14	190	134	89	166	5 2/8	3 2/4	6 4/8	D	3.5	7.72	0.87	1.11	4.61	1.4
LB14-B2	12	14	190	134	89	166	5 2/8	3 2/4	6 4/8	D	3.5	7.72	0.87	1.11	4.61	1.4
LB14L-A	12	14	190	134	89	166	5 2/8	3 2/4	6 4/8	B	3.5	7.72	0.87	1.11	4.61	1.4
LB14L-A1	12	14	190	134	89	166	5 2/8	3 2/4	6 4/8	E	3.5	7.72	0.87	1.11	4.61	1.4
LB14L-A2	12	14	190	134	89	166	5 2/8	3 2/4	6 4/8	D	3.5	7.72	0.87	1.11	4.61	1.4
EB14L-A2	12	14	190	134	89	166	5 2/8	3 2/4	6 4/8	D	3.8	8.38	0.87	1.11	4.91	1.4
LB14L-B2	12	14	190	134	89	166	5 2/8	3 2/4	6 4/8	D	3.5	7.72	0.87	1.11	4.61	1.4
SLB14L-A2 (with sensor)	12	14	190	134	89	166	5 2/8	3 2/4	6 4/8	D	3.5	7.72	0.87	1.11	4.61	1.4
SLB14L-B2 (with sensor)	12	14	190	134	89	166	5 2/8	3 2/4	6 4/8	D	3.5	7.72	0.87	1.11	4.61	1.4
LB14A-A1	12	14	190	134	89	176	5 2/8	3 2/4	6 7/8	B	3.55	7.83	0.87	1.11	4.66	1.4
LB14A-A2	12	14	190	134	89	176	5 2/8	3 2/4	6 7/8	D	3.55	7.83	0.87	1.11	4.66	1.4
LB16-B	12	19	240	175	100	155	6 7/8	4	6 1/8	B	4.45	9.81	1.26	1.61	6.06	1.9
LB16L-B	12	19	240	175	100	155	6 7/8	4	6 1/8	B	4.45	9.81	1.26	1.61	6.06	1.9
LB16L-A2	12	19	240	175	100	155	6 7/8	4	6 1/8	F/B	4.45	9.81	1.26	1.61	6.06	1.9

Model	Voltage V	Capacity C10 Ah	CCA		Dimension						Terminal	Weight(without acid)		Electrolyte		Total weight Kg	Charging current A
			@°F (-18°C)	A	mm(±2mm)			inch(±1/16in)				Kg	Lbs	Volume liters	Weight Kg		
			L	W	H	L	W	H									
LB16B-A	12	16	175	160	90	161	6 2/8	3 2/4	6 3/8	A	3.9	8.6	0.99	1.27	5.17	1.6	
LB16B-A1	12	16	175	160	90	161	6 2/8	3 2/4	6 3/8	C	3.9	8.6	0.99	1.27	5.17	1.6	
LB16B-A2	12	16	175	160	90	161	6 2/8	3 2/4	6 3/8	B	3.9	8.6	0.99	1.27	5.17	1.6	
LB16AL-A2	12	16	175	207	71.5	164	8 1/8	2 3/4	6 4/8	F	4	8.82	1.08	1.38	5.38	1.6	
HLB16A-A /HLB16A-AB	12	16	150	151	91	180	6	3 2/4	7 1/8	C	4.05	8.93	0.87	1.11	5.16	1.6	
LB16C-B	12	19	240	175	100	175	6 7/8	4	6 7/8	A	4.55	10	1.26	1.61	6.16	1.9	
LB16CL-B	12	19	240	175	100	175	6 7/8	4	6 7/8	A	4.55	10	1.26	1.61	6.16	1.9	
L50-N18L-A	12	20	260	205	90	162	8 1/8	3 2/4	6 3/8	C	4.95	10.9	1.32	1.69	6.64	2	
L50-N18L-A2	12	20	260	205	90	162	8 1/8	3 2/4	6 3/8	C	4.95	10.9	1.32	1.69	6.64	2	
L50-N18L-A3	12	20	260	205	90	162	8 1/8	3 2/4	6 3/8	A	4.95	10.9	1.32	1.69	6.64	2	
SL50-N18L-A (with sensor)	12	20	260	205	90	162	8 1/8	3 2/4	6 3/8	C	4.95	10.9	1.32	1.69	6.64	2	
SL50-N18L-A2 (with sensor)	12	20	260	205	90	162	8 1/8	3 2/4	6 3/8	C	4.95	10.9	1.32	1.69	6.64	2	
SL50-N18L-AT (with sensor)	12	20	260	205	90	162	8 1/8	3 2/4	6 3/8	C	4.95	10.9	1.32	1.69	6.64	2	
L50-N18A-A	12	20	260	205	90	176	8 1/8	3 2/4	6 7/8	C	5	11	1.32	1.69	6.69	2	
LB18-A	12	18	235	180	90	162	7 1/8	3 2/4	6 3/8	C	4.55	10	1.15	1.47	6.02	1.8	
LB18L-A	12	18	235	180	90	162	7 1/8	3 2/4	6 3/8	C	4.55	10	1.15	1.47	6.02	1.8	
LB18L-A2	12	18	235	180	90	162	7 1/8	3 2/4	6 3/8	C	4.55	10	1.15	1.47	6.02	1.8	
L60-N24-A	12	28	280	184	124	170	7 2/8	5	6 6/8	G	5.83	12.85	1.63	2.09	7.92	2.8	
L60-N24L-A	12	28	280	184	124	170	7 2/8	5	6 6/8	G	5.83	12.85	1.63	2.09	7.92	2.8	
L60-N24AL-B	12	28	280	184	124	170	7 2/8	5	6 6/8	G	5.83	12.85	1.63	2.09	7.92	2.8	
SL60-N24AL-B (with sensor)	12	28	280	184	124	170	7 2/8	5	6 6/8	G	5.83	12.85	1.63	2.09	7.92	2.8	
L60-N28L-A	12	28	280	184	130	170	7 2/8	5	6 6/8	G	5.9	13.01	1.65	2.11	8.01	2.8	
L60-N30L-A	12	30	300	184	130	170	7 2/8	5	6 6/8	G	6.35	14	1.59	2.04	8.39	3	
L60-N30-A	12	30	300	184	130	170	7 2/8	5	6 6/8	G	6.35	14	1.59	2.04	8.39	3	

L60-N30L-B	12	30	300	184	130	170	7 2/8	5	6 6/8	G	6.35	14	1.59	2.04	8.39	3
------------	----	----	-----	-----	-----	-----	----------	---	----------	---	------	----	------	------	------	---

Model	Voltage V	Capacity C10 Ah	CCA @°F (- 18°C) A	Dimension						Terminal	Weight(without acid)		Electrolyte		Total weight Kg	Charging current A
				mm(±2mm)			inch(±1/16in)				Kg	Lbs	Volume liters	Weight Kg		
				L	W	H	L	W	H							
LB30L-B	12	30	300	165	130	176	6 4/8	5	6 7/8	A	6.3	13.89	1.57	2.01	8.31	3
LB30CL-B	12	30	300	165	130	192	6 4/8	5	7 4/8	A	6.35	14	1.57	2.01	8.36	3
U1-5	12	12	120	195	130	180	7 5/8	5	7 1/8	G	3.95	8.71	2.2	2.82	6.77	1.2
U1-6	12	16	180	195	130	180	7 5/8	5	7 1/8	G	3.95	8.71	2.2	2.82	6.77	1.2
U1R-5	12	12	120	195	130	180	7 5/8	5	7 1/8	G	3.95	8.71	2.2	2.82	6.77	1.2
U1R-6	12	16	180	195	130	180	7 5/8	5	7 1/8	G	3.95	8.71	2.2	2.82	6.77	1.2
U1-7	12	18	180	195	130	180	7 5/8	5	7 1/8	G	4.95	10.9	2.1	2.69	7.64	1.8
U1R-7	12	18	180	195	130	180	7 5/8	5	7 1/8	G	4.95	10.9	2.1	2.69	7.64	1.8
U1-9	12	24	240	195	130	180	7 5/8	5	7 1/8	G	5.85	12.9	2	2.56	8.41	2.4
U1R-9	12	24	240	195	130	180	7 5/8	5	7 1/8	G	5.85	12.9	2	2.56	8.41	2.4
U1-11	12	30	300	195	130	180	7 5/8	5	7 1/8	G	6.85	15.1	1.9	2.43	9.28	3
U1R-11	12	30	300	195	130	180	7 5/8	5	7 1/8	G	6.85	15.1	1.9	2.43	9.28	3

Conventional Flooded

General Features

1. High Capacity, Long life.
2. High CCA and good starting performance.
3. Good charging acceptance and vibration resistant performance.
4. High-quality composite of Fiber Glass and PE separators Application.
5. Application of TTP technology.
6. Advanced sulfate-resistant technology.
7. Adopt advanced low antimony alloy and low maintenance design.
8. Seal design with reliable plugs.
9. Dry charged design, long storage time, can be used at any time you want.
10. full ranges models, good appearance and high standard design.

Typical Applications

1. ATV.
2. Jet ski
3. Motorcycle
4. Snowmobile
5. Lawn & Garden

Specifications

Model	Nominal Voltage (V)	Capacity (10Hr) AH	CCA	Battery Size							Terminal Type	Weight		Electrlyte		Total	Rehular		
			@°F	Dimensions-Millimetres (±2mm)			Dimensions_Incheses (±1/16in)			Acid		W/O		Volume	Weight	Weight	Charge		
			(-18°C)	L	W	H	L	W	H			Kg	Lbs			liters	Kg	For battery	Current
			A															Kg	A
6N2-2A	6	2	N/A	70	47	96	2 3/4	1 3/4	3 3/4	/	0.41			0.9	0.12			0.15	0.56
6N2-2A-1	6	2	N/A	70	47	96	2 3/4	1 3/4	3 3/4	/	0.41	0.9	0.12	0.15	0.56	0.2			
6N2-2A-2	6	2	N/A	70	47	96	2 3/4	1 3/4	3 3/4	/	0.41	0.9	0.12	0.15	0.56	0.2			
6N2-2A-3	6	2	N/A	70	47	96	2 3/4	1 3/4	3 3/4	/	0.41	0.9	0.12	0.15	0.56	0.2			
6N2-2A-4	6	2	N/A	70	47	96	2 3/4	1 3/4	3 3/4	/	0.41	0.9	0.12	0.15	0.56	0.2			
6N2-2A-5	6	2	N/A	70	47	96	2 3/4	1 3/4	3 3/4	/	0.41	0.9	0.12	0.15	0.56	0.2			
6N2-2A-6	6	2	N/A	70	47	96	2 3/4	1 3/4	3 3/4	/	0.41	0.9	0.12	0.15	0.56	0.2			
6N2-2A-7	6	2	N/A	70	47	96	2 3/4	1 3/4	3 3/4	/	0.41	0.9	0.12	0.15	0.56	0.2			
6N2-2A-8	6	2	N/A	70	47	96	2 3/4	1 3/4	3 3/4	/	0.41	0.9	0.12	0.15	0.56	0.2			
6N2-2D	6	2	N/A	70	47	104	2 3/4	1 3/4	4 1/8	/	0.42	0.93	0.12	0.15	0.57	0.2			
6N2A-2C	6	2	N/A	70	47	106	2 3/4	1 3/4	4 1/8	/	0.42	0.93	0.12	0.15	0.57	0.2			
6N2A-2C-1	6	2	N/A	70	47	106	2 3/4	1 3/4	4 1/8	/	0.42	0.93	0.12	0.15	0.57	0.2			
6N4-2A	6	4	N/A	71	71	96	2 3/4	2 3/4	3 3/4	/	0.61	1.34	0.19	0.25	0.86	0.4			
6N4-2A-C1	6	4	N/A	71	71	96	2 3/4	2 3/4	3 3/4	/	0.61	1.34	0.19	0.25	0.86	0.6			
6N4-2A-2	6	4	N/A	71	71	96	2 3/4	2 3/4	3 3/4	/	0.61	1.34	0.19	0.25	0.86	0.4			
6N4-2A-3	6	4	N/A	71	71	96	2 3/4	2 3/4	3 3/4	/	0.61	1.34	0.19	0.25	0.86	0.4			
6N4-2A-4	6	4	N/A	71	71	96	2 3/4	2 3/4	3 3/4	/	0.61	1.34	0.19	0.25	0.86	0.4			
6N4-2A-5	6	4	N/A	71	71	96	2 3/4	2 3/4	3 3/4	/	0.61	1.34	0.19	0.25	0.86	0.4			
6N4-2A-6	6	4	N/A	71	71	96	2 3/4	2 3/4	3 3/4	/	0.61	1.34	0.19	0.25	0.86	0.4			
6N4-2A-7	6	4	N/A	71	71	96	2 3/4	2 3/4	3 3/4	/	0.61	1.34	0.19	0.25	0.86	0.4			
6N4-2A-8	6	4	N/A	71	71	96	2 3/4	2 3/4	3 3/4	/	0.61	1.34	0.19	0.25	0.86	0.4			
6N4C-1B	6	4	N/A	71	71	105	2 3/4	2 3/4	4 1/8	/	0.61	1.34	0.19	0.25	0.86	0.4			
6N4A-4D	6	4	N/A	61	57	131	2 3/8	2 1/4	5 1/8	/	0.68	1.5	0.17	0.22	0.9	0.4			
6N4A-4D-1	6	4	N/A	61	57	131	2 3/8	2 1/4	5 1/8	/	0.68	1.5	0.17	0.22	0.9	0.4			
6N4B-2A	6	4	N/A	102	48	96	4	2	3 3/4	/	0.6	1.32	0.19	0.25	0.85	0.4			

Model	Nominal Voltage (V)	Capacity (10Hr) AH	CCA	Battery Size							Terminal Type	Weight		Electrlyte		Total	Rehular		
			@°F	Dimensions-Millimetres (±2mm)			Dimensions_Incheses (±1/16in)			Acid		W/O		Volume	Weight	Weight	Charge		
			(-18°C)	L	W	H	L	W	H			Kg	Lbs			liters	Kg	For battery	Current
			A															Kg	A
6N4B-2A-1	6	4	N/A	102	48	96	4	2	3 3/4	/	0.6			1.32	0.19			0.25	0.85

6N4B-2A-2	6	4	N/A	102	48	96	4	2	3 3/4	/	0.6	1.32	0.19	0.25	0.85	0.4
6N4B-2A-3	6	4	N/A	102	48	96	4	2	3 3/4	/	0.6	1.32	0.19	0.25	0.85	0.4
6N4B-2A-4	6	4	N/A	102	48	96	4	2	3 3/4	/	0.6	1.32	0.19	0.25	0.85	0.6
6N4B-2A-5	6	4	N/A	102	48	96	4	2	3 3/4	/	0.6	1.32	0.19	0.25	0.85	0.6
6N5.5-3D	6	5.5	N/A	90	70	100	3 1/2	2 3/4	3 7/8	/	0.8	1.76	0.27	0.35	1.15	0.6
6N5.5-1D	6	5.5	N/A	90	70	100	3 1/2	2 3/4	3 7/8	/	0.8	1.76	0.27	0.35	1.15	0.6
6N5.5-1D-1	6	5.5	N/A	90	70	100	3 1/2	2 3/4	3 7/8	/	0.8	1.76	0.27	0.35	1.15	0.6
6N6-1B	6	6	N/A	99	57	111	3 7/8	2 1/4	4 3/8	/	0.81	1.79	0.27	0.35	1.16	0.6
6N6-1B-1	6	6	N/A	99	57	111	3 7/8	2 1/4	4 3/8	/	0.81	1.79	0.27	0.35	1.16	0.6
6N6-3B	6	6	N/A	99	57	111	3 7/8	2 1/4	4 3/8	B	0.82	1.81	0.27	0.35	1.17	0.6
6N6-3B-1	6	6	N/A	99	57	111	3 7/8	2 1/4	4 3/8	B	0.82	1.81	0.27	0.35	1.17	0.6
6N6-1D	6	6	N/A	99	57	111	3 7/8	2 1/4	4 3/8	/	0.81	1.79	0.27	0.35	1.16	0.6
6N6-1D-1	6	6	N/A	99	57	111	3 7/8	2 1/4	4 3/8	/	0.81	1.79	0.27	0.35	1.16	0.6
6N6-1D-2	6	6	N/A	99	57	111	3 7/8	2 1/4	4 3/8	/	0.81	1.79	0.27	0.35	1.16	0.6
6N6-1C	6	6	N/A	99	57	111	3 7/8	2 1/4	4 3/8	/	0.81	1.79	0.27	0.35	1.16	0.6
B39-6	6	7	N/A	126	48	126	5	2	5	B	1.1	2.43	0.35	0.45	1.55	0.7
B49-6	6	10	N/A	91	83	160	3 5/8	3 1/4	6 1/4	B	1.5	3.31	0.57	0.73	2.23	1
B38-6A	6	13	N/A	119	83	161	4 5/8	3 1/4	6 3/8	B	1.9	4.19	0.75	0.96	2.86	1.3
6N11-2D	6	11	N/A	150	70	100	5 7/8	2 3/4	3 7/8	B	1.38	3.04	0.42	0.54	1.92	1.1
6LB11-2D	6	11	N/A	150	70	100	5 7/8	2 3/4	3 7/8	B	1.38	3.04	0.42	0.54	1.92	1.1
6N11A-1B	6	11	N/A	122	62	131	4 3/4	2 1/2	5 1/8	B	1.4	3.09	0.48	0.61	2.01	1.1
6N11A-3	6	11	N/A	122	62	131	4 3/4	2 1/2	5 1/8	B	1.4	3.09	0.44	0.56	1.96	1.1
6N11A-4	6	11	N/A	122	62	131	4 3/4	2 1/2	5 1/8	B	1.4	3.09	0.44	0.56	1.96	1.1
6N11A-3A	6	11	N/A	122	62	131	4 3/4	2 1/2	5 1/8	B	1.4	3.09	0.44	0.56	1.96	1.1

Model	Nominal Voltage (V)	Capacity (10Hr) AH	CCA							Terminal Type	Weight W/O		Electrlyte		Total Weight	Rehular Charge	
			@°F								Acid	Volume	Weight	For battery			Current
			(-18°C)	Dimensions-Millimetres (±2mm)				Dimensions_Incheses (±1/16in)							Kg	Lbs	
				A	L	W	H	L	W		H						
6N11A-3B	6	11	N/A	122	62	131	4 3/4	2 1/2	5 1/8	B	1.4	3.09	0.44	0.56	1.96	1.1	
6N11A-4A	6	11	N/A	122	62	131	4 3/4	2 1/2	5 1/8	B	1.4	3.09	0.44	0.56	1.96	1.1	
B54-6	6	12	N/A	156	57	116	6 1/8	2 1/4	4 5/8	B	1.5	3.31	0.39	0.5	2	1.2	
B54-6A	6	12	N/A	156	57	116	6 1/8	2 1/4	4 5/8	B	1.5	3.31	0.39	0.5	2	1.2	
6N12-1B	6	12	N/A	104	75	140	4 1/8	3	5 1/2	B	1.65	3.64	0.53	0.68	2.33	1.2	
6LB8L-B	6	8	N/A	120	70	95	4 3/4	2 3/4	3 3/4	B	1.15	2.54	0.3	0.38	1.53	0.8	
12N3-3A	12	3	24	98	56	110	3 7/8	2 1/4	4 3/8	B	0.95	2.09	0.23	0.29	1.24	0.3	

12N4-3B	12	4	30	120	70	92	4 3/4	2 3/4	3 5/8	A	1.2	2.65	0.3	0.38	1.58	0.4
12N5-3B	12	5	40	120	60	130	4 3/4	2 1/4	5 1/8	B	1.53	3.37	0.36	0.46	1.99	0.5
12N5-3B2	12	5	40	120	60	130	4 3/4	2 1/4	5 1/8	A	1.58	3.48	0.36	0.46	2.04	0.5
12N5-4B	12	5	40	120	60	130	4 3/4	2 1/4	5 1/8	B	1.53	3.37	0.36	0.46	1.99	0.5
12N5.5-3B	12	5.5	44	135	60	130	5 3/8	2 1/4	5 1/8	B	1.55	3.42	0.43	0.55	2.1	0.6
12N5.5-4A	12	5.5	44	135	60	130	5 3/8	2 1/4	5 1/8	F	1.55	3.42	0.43	0.55	2.1	0.6
12N5.5-4A-1	12	5.5	44	135	60	130	5 3/8	2 1/4	5 1/8	B	1.55	3.42	0.43	0.55	2.1	0.6
12N5.5-4B	12	5.5	44	135	60	130	5 3/8	2 1/4	5 1/8	B	1.55	3.42	0.43	0.55	2.1	0.6
12N5.5A-3B	12	5.5	44	103	90	114	4	3 1/2	4 1/2	B	1.65	3.64	0.48	0.61	2.26	0.6
12N6-3B	12	6	50	137	72	95	5 3/8	2 3/4	3 3/4	B	1.55	3.42	0.39	0.5	2.05	0.6
12N6-4A	12	6	50	137	72	95	5 3/8	2 3/4	3 3/4	B	1.55	3.42	0.39	0.5	2.05	0.6
12N6-4B	12	6	50	137	72	95	5 3/8	2 3/4	3 3/4	B	1.55	3.42	0.39	0.5	2.05	0.6
12N6.5-3B	12	6.5	55	137	72	107	5 3/8	2 3/4	4 1/4	B	1.7	3.75	0.45	0.58	2.28	0.7
12N6.5A-4B	12	7	55	137	72	118	5 3/8	2 3/4	4 5/8	B	1.77	3.9	0.43	0.54	2.31	1.2
12N7E-B	12	6	55	150	87	95	5 7/8	3 1/2	3 3/4	D	2	4.41	0.45	0.58	2.58	1.2
12N7-3A	12	7	74	135	75	133	5 3/8	3	5 2/8	B	2.16	4.76	0.54	0.69	2.85	0.7
12N7-3A2	12	7	74	135	75	133	5 3/8	3	5 2/8	A	2.18	4.81	0.54	0.69	2.87	0.7
12N7-3B	12	7	74	135	75	133	5 3/8	3	5 2/8	B	2.16	4.76	0.54	0.69	2.85	0.7

Model	Nominal Voltage (V)	Capacity (10Hr) AH	CCA		Battery Size						Weight		Electrlyte		Total Weight	Rehular Charge	
			@°F		Dimensions-Millimetres (±2mm)			Dimensions_Inches (±1/16in)			Terminal Type	W/O		Volume	Weight	For battery	Current
			(-18°C)	A	L	W	H	L	W	H		Kg	Lbs				
12N7-3B2	12	7	74	135	75	133	5 3/8	3	5 2/8	A	2.18	4.81	0.54	0.69	2.87	0.7	
12N7-4A	12	7	74	135	75	133	5 3/8	3	5 2/8	B	2.16	4.76	0.54	0.69	2.85	0.7	
12N7-4A2	12	7	74	135	75	133	5 3/8	3	5 2/8	A	2.18	4.81	0.54	0.69	2.87	0.7	
12N7-4B	12	7	74	135	75	133	5 3/8	3	5 2/8	B	2.16	4.76	0.54	0.69	2.85	0.7	
12N7D-3B	12	7	74	135	75	150	5 3/8	3	5 7/8	B	2.18	4.81	0.54	0.69	2.87	0.7	
12N7A-3A	12	7	70	150	60	130	5 7/8	2 1/4	5 1/8	B	1.9	4.19	0.51	0.65	2.55	1.2	
/12N7B-3A																	
12N7A-4A	12	7	70	150	60	130	5 7/8	2 1/4	5 1/8	B	1.9	4.19	0.51	0.65	2.55	1.2	
/12N7B-4A																	
12N7B-3B	12	7	70	150	60	130	5 7/8	2 1/4	5 1/8	B	1.9	4.19	0.51	0.65	2.55	1.2	
12N7B-4B	12	7	70	150	60	130	6	2 1/3	5 1/8	B	1.9	4.19	0.51	0.65	2.55	0.7	
12N7C-3D	12	7	74	130	90	114	5 1/8	3 1/2	4 1/2	E	2.15	4.74	0.58	0.74	2.89	0.7	
12N7CZ-3D	12	8	74	130	90	114	5	3 1/2	4 1/2	E	2.15	4.74	0.58	0.74	2.89	0.8	

12N9-3A	12	9	85	135	75	139	5 1/4	3	5 1/2	B	2.4	5.29	0.56	0.72	3.12	0.9
12N9-3A-1	12	9	85	135	75	139	5 1/4	3	5 1/2	B	2.4	5.29	0.56	0.72	3.12	0.9
12N9-3B	12	9	85	135	75	139	5 1/4	3	5 1/2	B	2.4	5.29	0.56	0.72	3.12	0.9
12N9-4B-1	12	9	85	135	75	139	5 1/4	3	5 1/2	B	2.4	5.29	0.56	0.72	3.12	0.9
12N10-3A	12	10	95	135	90	145	5 1/4	3 1/2	5 3/4	B	3.15	6.94	0.7	0.9	4.05	1
12N10-3A-1	12	10	95	135	90	145	5 1/4	3 1/2	5 3/4	B	3.15	6.94	0.7	0.9	4.05	1
12N10-3A-2	12	10	95	135	90	145	5 1/4	3 1/2	5 3/4	D	3.15	6.94	0.7	0.9	4.05	1
12N10-3B	12	10	95	135	90	145	5 1/4	3 1/2	5 3/4	B	3.15	6.94	0.7	0.9	4.05	1
12N10-3B-1	12	10	95	135	90	145	5 1/4	3 1/2	5 3/4	A	3.15	6.94	0.7	0.9	4.05	1
12N11-3A	12	11	103	135	90	155	5 1/4	3 1/2	6	B	3.2	7.05	0.72	0.92	4.12	1.1
12N11-3A-1	12	11	103	135	90	155	5 1/4	3 1/2	6	D	3.2	7.05	0.72	0.92	4.12	1.1
12N11-3B	12	11	103	135	90	155	5 1/4	3 1/2	6	B	3.2	7.05	0.72	0.92	4.12	1.1

Model	Nominal Voltage (V)	Capacity (10Hr) AH	Battery Size							Terminal Type	Weight		Electrlyte		Total	Rehular							
			CCA @°F (-18°C)	Dimensions-Millimetres (±2mm)				Dimensions_Inches (±1/16in)			W/O	Acid	Volume	Weight	For battery	Current							
																	A	L	W	H	L	W	H
12N12-3A	12	12	113	202	76	134	8	3	5 1/4	B	3.1	6.83	0.77	0.98	4.08	1.2							
12N12-3B	12	12	113	202	76	134	8	3	5 1/4	B	3.1	6.83	0.77	0.98	4.08	1.2							
12N12A-4A-1	12	12	113	134	80	160	5 1/4	3 1/8	6 1/4	B	3.25	7.16	0.7	0.9	4.15	1.2							
12N12A-4A-1(J)	12	12	113	134	80	160	5 1/4	3 1/8	6 1/4	B	3	6.61	0.72	0.92	3.92	1.2							
12N14-3A	12	14	128	134	89	166	5 1/4	3 1/2	6 1/2	B	3.5	7.72	0.8	1.02	4.52	1.4							
12N14-3B	12	14	128	134	89	166	5 1/4	3 1/2	6 1/2	D	3.5	7.72	0.8	1.02	4.52	1.4							
12N14-3A2	12	14	128	134	89	166	5 1/4	3 1/2	6 1/2	D	3.5	7.72	0.8	1.02	4.52	1.4							
12N16-3A	12	16	145	175	100	155	7	3 7/8	6	B	4	8.82	1.2	1.54	5.54	1.6							
12N16-3B	12	16	145	175	100	155	7	3 7/8	6	B	4	8.82	1.2	1.54	5.54	1.6							
12N16-4B	12	16	145	175	100	155	7	3 7/8	6	B	4	8.82	1.2	1.54	5.54	1.6							
12C16A-3A	12	19	210	186	82	171	7 1/4	3 1/4	6 3/4	G	4.65	10.25	1.04	1.33	5.98	1.9							
12C16A-3B	12	19	210	186	82	171	7 1/4	3 1/4	6 3/4	G	4.65	10.25	1.04	1.33	5.98	1.9							
12N18-3	12	18	164	205	90	162	8	3 1/2	6 1/2	B	4.25	9.37	1.25	1.6	5.85	1.8							
12N18-3-1	12	18	164	205	90	162	8	3 1/2	6 1/2	C	4.25	9.37	1.25	1.6	5.85	1.8							
12N18-3A	12	18	164	205	90	162	8	3 1/2	6 1/2	C	4.25	9.37	1.25	1.6	5.85	1.8							
12N18-4A	12	18	164	205	90	162	8	3 1/2	6 1/2	C	4.25	9.37	1.25	1.6	5.85	1.8							
12N18-3B	12	18	164	205	90	162	8	3 1/2	6 1/2	C	4.25	9.37	1.25	1.6	5.85	1.8							
12N24-3	12	24	218	184	124	175	7 1/4	4 7/8	7	G	5.33	11.75	1.72	2.2	7.53	2.4							
12N24-4	12	24	218	184	124	175	7 1/4	4 7/8	7	G	5.33	11.75	1.72	2.2	7.53	2.4							

12N24-3A	12	24	218	184	124	175	7 1/4	4 7/8	7	G	5.33	11.75	1.72	2.2	7.53	2.4
12N24-4A	12	24	218	184	124	175	7 1/4	4 7/8	7	G	5.33	11.75	1.72	2.2	7.53	2.4
CHD4-12	12	28	280	205	130	165	8 1/8	5 1/8	6 1/2	H	6.03	13.29	2.03	2.6	8.63	2.8